

Seated Electric Reach Truck

| Manufacturer | | NEOlift | |
|--|---------|-----------------|-----------------|
| Model | | NRS16 | NRS20 |
| Power type | | Battery | Battery |
| Operation type | | Seated | Seated |
| Rated capacity | kg | 1600 | 2000 |
| Load center | mm | 600 | 600 |
| Front overhang | mm | 160 | 160 |
| Wheelbase | mm | 1495 | 1665 |
| Service weight(incl. battery) | kg | 3320 | 3600 |
| Wheel type | | PU | PU |
| Load wheel | mm | φ267*114 | φ267*114 |
| Drive wheel | mm | φ343*135 | φ343*135 |
| Number of wheels,front/rear(x=drive wheel) | | 2/ 1X | 2/ 1X |
| Wheel tread,load side | mm | 1158 | 1158 |
| Fork tilt | ° | 3/5 | 3/5 |
| Mast closed height | mm | 3210 | 3210 |
| Free Lift height | mm | 2225 | 2225 |
| Lift height | mm | 7500 | 7500 |
| Mast extended height with load-backrest | mm | 8485 | 8485 |
| Overhead guard height | mm | 2200 | 2200 |
| Pedal height | mm | 530 | 530 |
| Overall length | mm | 2440 | 2500 |
| Overall width | mm | 1270 | 1270 |
| Fork size | mm | 1070×100×35 | 1070×122×40 |
| Fork outside width | mm | 210-800 | 260-820 |
| Body ground clearance | mm | 80 | 80 |
| Aisle width for pallet 1000*1000mm | Ast(mm) | 2745 | 2975 |
| Turning radius | Wa(mm) | 1775 | 1945 |
| Driving speed(load/unload) | km/h | 7.5/8 | 7.5/8 |
| Lifting speed(load/unload) | mm/s | 150/260 | 150/260 |
| Lowering speed(load/unload) | mm/s | 300/160 | 300/160 |
| Max.gradeability(load/unload) | % | 8/10 | 6/8 |
| Brake type | | Electromagnetic | Electromagnetic |
| Driving Motor(S2-60min) | kw | 4.5 | 6.5 |
| Lifting Motor(S3-15%) | kw | 6.3 | 8.6 |
| Battery voltage/capacity | V/Ah | 48/400 | 48/460 |
| Battery weight | kg | 700 | 800 |
| Steering system | | EPS | EPS |